Hexagon Head Cap Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-00-085-3093



**Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** 0.875 inches **Fastener Length:** Between 1.220 inches and 1.250 inches **Head Style:** Distorted head **Head Height:** Between 0.188 inches and 0.198 inches Width Between Flats: Between 0.489 inches and 0.500 inches Locking Feature: Distortions head **Thread Diameter:** 0.312 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c and 38.0 rockwell c **Product Name:** Navy special project Material:

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536

## Thread Series Designator:

Unc Shelf Life: N/a Unit Of Measure: --Demilitarization:

No

Fiig:

A003b0