NSN 5305-00-086-7034

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-086-7034

| Thread Class: |
|----------------------------------------------------------------------|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 1.148 inches and 1.190 inches |
| Fastener Length: |
| Between 1.190 inches and 1.250 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.166 inches and 0.183 inches |
| Head Height: |
| Between 0.073 inches and 0.079 inches |
| Hole Diameter: |
| 0.037 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.112 inches |
| Hole Quantity: |
| 1 |
| Thready Qty Per Inch (tpi): |
| 4 |
| Min. Tensile Strength (psi): |
| 60000 pounds per square inch |
| Screw Material: |
| Steel |
| Screw Surface Treatment: |
| Cadmium and chromate |
| Screw Surface Treatment Specification: |
| Qq-p-416 type 2 cl 3 federal specification single treatment response |
| Head Hole Configuration Style: |
| Round |
| Thread Series Designator: |
| Unf |
| Specification Or Standard: |
| 1 type and 5s style |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5305-00-086-7034

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0