## NSN 5305-00-086-7865

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-086-7865 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 0.699 inches and 0.729 inches **Head Style:** Pan **Head Diameter:** Between 0.238 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Product Name:** Navy special project **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5732 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Data:** 80205-nas1631 professional/industrial association standard

**Shelf Life:** N/a

**Unit Of Measure:** 

--

## NSN 5305-00-086-7865

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0