NSN 5305-00-087-3079

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-087-3079 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** 1.060 inches **Head Style:** Flat chamfer **Head Diameter:** 0.375 inches **Head Height:** 0.240 inches **First Diameter From Head:** Between 0.135 inches and 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.680 inches **Point Style:** Cone **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Color: Black Material: Steel comp 4037 **Material Specification:** Ams6300 assn standard single material response **Surface Treatment:** Oxide

Surface Treatment Specification:

Mil-c-13924 cl 3 military specification single treatment response

NSN 5305-00-087-3079

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-c-13924 spec.