## NSN 5305-00-089-0049

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-089-0049 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.265 inches and 0.358 inches **Fastener Length:** Between 0.407 inches and 0.438 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.322 inches and 0.385 inches **Locking Feature:** Patch threads or strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch **Hardness Rating:** 248.0 brinell standard and 321.0 brinell standard **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5735 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1189 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-089-0049

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0