NSN 5305-00-089-0268

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-089-0268 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **Hole Diameter:** 0.031 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.093 inches and 0.095 inches **Hole Quantity:** 2 **Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Hole Configuration Style:** Round internal hexagon Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:**

ourrace freatment opecinication.

Qq-p-416 type 2 cl 3 federal specification single treatment response

NSN 5305-00-089-0268

Socket Head Cap Screw - Page 2 of 2



Inread Series Designator:
Unc
Specification Data:
80205-nas1352 professional/industrial association standard
Departure From Cited Designator:
As modified by head data
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0