

View Online at <https://aerobasegroup.com/nsn/5305-00-089-9445>

Thread Direction:

Right-hand

Thread Length:

Between 0.402 inches and 0.438 inches

Fastener Length:

Between 2.418 inches and 2.438 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.126 inches and 0.141 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Locking Feature:

Detent ball grip

Grip Diameter:

Between 0.2483 inches and 0.2492 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Grip Length:

Between 2.000 inches and 2.016 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

39.0 rockwell c fastener and 45.0 rockwell c fastener

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.323 inches first hole and 2.343 inches first hole

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response fastener

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0