NSN 5305-00-092-6682

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-092-6682

view Online at https://aerobasegroup.com/nsn/5305-00-092-6682
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.278 inches and 0.329 inches
Fastener Length:
Between 1.231 inches and 1.251 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.477 inches and 0.492 inches
Head Height:
Between 0.126 inches and 0.141 inches
Locking Feature:
Detent ball fastener
Grip Diameter:
Between 0.2487 inches and 0.2492 inches
Shank Unthreaded Hole Diameter:
0.076 inches and 0.086 inches first hole
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Grip Length:
Between 0.812 inches and 0.828 inches
Thready Qty Per Inch (tpi):
28
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.135 inches and 1.155 inches first hole
Surface Finish:
32.0 microinches grip
Product Name:
Navy special project
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-00-092-6682

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0