## NSN 5305-00-093-6683

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-093-6683 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.293 inches and 0.314 inches **Fastener Length:** Between 1.481 inches and 1.501 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.126 inches and 0.141 inches **Locking Feature:** Detent ball fastener **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.062 inches and 1.078 inches Thready Qty Per Inch (tpi): Distance From Head Largest Bearing Surface To Shank Hole Center: 1.385 inches first hole and 1.405 inches first hole **Surface Finish:** 32.0 microinches grip **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-00-093-6683

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0