## NSN 5305-00-093-6685

Close Tolerance Screw - Page 1 of 2

---



View Online at https://aerobasegroup.com/nsn/5305-00-093-6685

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.277 inches and 0.328 inches
Fastener Length:
Between 1.356 inches and 1.376 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.477 inches and 0.492 inches
Head Height:
Between 0.126 inches and 0.141 inches
Locking Feature:
Detent ball fastener
Grip Diameter:
Between 0.2487 inches and 0.2492 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.086 inches first hole
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Grip Length:
Between 0.938 inches and 0.954 inches
Thready Qty Per Inch (tpi):
28
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.261 inches first hole and 1.281 inches first hole
Surface Finish:
32.0 microinches grip
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
-

## NSN 5305-00-093-6685

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

