NSN 5305-00-094-2126

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-094-2126 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.906 inches **Fastener Length:** 2.125 inches **Head Style:** Flat countersunk **Head Diameter:** Between 1.135 inches and 1.145 inches **Shoulder Diameter:** 0.686 inches first shoulder and 0.687 inches first shoulder **Shoulder Length:** 1.037 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: Between 0.501 inches and 0.504 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp 4130 **Surface Treatment:** Cadmium and chromate Q-p-416 federal specification 13th treatment response head

Surface Treatment Specification: Thread Series Designator: Unf Shelf Life: N/a **Unit Of Measure:**

NSN 5305-00-094-2126

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0