NSN 5305-00-094-3430

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-094-3430



Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.245 inches and 0.326 inches

Fastener Length:

Between 0.344 inches and 0.375 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.191 inches and 0.225 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

80000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Stainless steel

Screw Material Specification:

Qq-s-763, 300 series federal specification single material response or 66, 300 series federal standard single material response or comp

16-18 or 18-8 assn standard single material response

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-c-13924, cl 4 military specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 3c style

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

NSN 5305-00-094-3430

Machine Screw - Page 2 of 2

Mil-std (military Standard):

Mil-c-13924 spec.

