

View Online at <https://aerobasegroup.com/nsn/5305-00-095-3634>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.620 inches

Fastener Length:

2.500 inches

Head Style:

Pan no. 2

Head Diameter:

Between 1.182 inches and 1.192 inches

Head Height:

Between 0.180 inches and 0.190 inches

Shoulder Length:

1.870 inches first shoulder and 1.890 inches first shoulder

Shank Unthreaded Hole Diameter:

0.115 inches first hole and 0.135 inches first hole

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

35.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.350 inches first hole and 2.370 inches first hole

Shoulder Shape:

Round first shoulder

Special Features:

Hole drilled in thd end 0.375 in. Dia; 0.375 in. Min 0.415 in. Maximum depth; countersunk 60 deg; 2 drilled holes for cotter pin

Material:

Steel comp 8750

Surface Treatment:

Tin

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0