## NSN 5305-00-095-3634

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-095-3634 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.620 inches **Fastener Length:** 2.500 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 1.182 inches and 1.192 inches **Head Height:** Between 0.180 inches and 0.190 inches **Shoulder Length:** 1.870 inches first shoulder and 1.890 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.115 inches first hole and 0.135 inches first hole **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.750 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 35.0 rockwell c and 40.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 2.350 inches first hole and 2.370 inches first hole **Shoulder Shape:** Round first shoulder **Special Features:** Hole drilled in thd end 0.375 in. Dia; 0.375 in. Min 0.415 in. Maximum depth; countersunk 60 deg; 2 drilled holes for cotter pin Material: Steel comp 8750 **Surface Treatment:** Tin **Thread Series Designator:** Unf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-00-095-3634

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0