## NSN 5305-00-096-1641

Externally Relieved Body Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-00-096-1641            |
|--|
| Thread Class:  |
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.125 inches   |
| Fastener Length:   |
| 0.302 inches   |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| 0.219 inches   |
| Head Height:   |
| 0.045 inches   |
| First Diameter From Head:  |
| 0.124 inches   |
| Second Diameter From Head:   |
| 0.084 inches   |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter:  |
| 0.146 inches   |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| 0.177 inches   |
| Internal Drive Style:  |
| Slot   |
| Thread Diameter:   |
| 0.112 inches   |
| Thready Qty Per Inch (tpi):  |
| 48   |
| Externally Relieved Body Diameter Quantity:                              |
| 2  |
| Material:  |
| Copper alloy   |
| Surface Treatment:   |
| Nickel   |
| Thread Series Designator:  |
| Unf  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |

No

## NSN 5305-00-096-1641

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0