NSN 5305-00-096-1642

Externally Relieved Body Screw - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5305-00-096-1642 |
|--|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.120 inches |
| Fastener Length: |
| 0.185 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.124 inches and 0.126 inches |
| Head Height: |
| Between 0.045 inches and 0.046 inches |
| First Diameter From Head: |
| 0.092 inches |
| Second Diameter From Head: |
| Between 0.050 inches and 0.054 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| Between 0.045 inches and 0.048 inches |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| Between 0.065 inches and 0.068 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.073 inches |
| Thready Qty Per Inch (tpi): |
| 64 |
| Externally Relieved Body Diameter Quantity: |
| 2 |
| Material: |
| Copper alloy |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A003b0