NSN 5305-00-097-4452

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-097-4452 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.374 inches and 0.434 inches **Fastener Length:** Between 0.829 inches and 0.859 inches **Head Style:** Flat countersunk **Head Diameter:** 0.357 inches **Shoulder Diameter:** 0.254 inches first shoulder and 0.256 inches first shoulder **Shoulder Length:** 0.376 inches first shoulder and 0.406 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 33.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Color dark blue Material: Steel comp 4037 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:**

Unf

Shelf Life:

N/a

NSN 5305-00-097-4452

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0