NSN 5305-00-097-4484



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-097-4484 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.277 inches and 0.328 inches **Fastener Length:** Between 2.168 inches and 2.188 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.126 inches and 0.141 inches **Locking Feature:** Detent ball grip **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches and 0.086 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.750 inches and 1.766 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 2.073 inches and 2.093 inches first hole **Surface Finish:** 32.0 microinches grip **Product Name:** Navy special project Material:

Steel comp 302 spring

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

NSN 5305-00-097-4484

Close Tolerance Screw - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0