

View Online at <https://aerobasegroup.com/nsn/5305-00-097-4593>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.901 inches and 1.116 inches

Fastener Length:

Between 0.984 inches and 1.016 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.550 inches and 0.563 inches

Head Height:

Between 0.368 inches and 0.375 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.375 inches

Width Across Flats:

Between 0.312 inches and 0.316 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel

Material Specification:

66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66 federal standard 4th material response or 66 federal standard 5th material response or astm-a493 aisi xm-7 assn standard 6th material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 cl 4 military specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

6 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.