NSN 5305-00-099-7643



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-099-7643 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.277 inches and 0.328 inches **Fastener Length:** Between 2.043 inches and 2.063 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.126 inches and 0.141 inches **Locking Feature:** Detent ball grip **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches and 0.086 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.625 inches and 1.641 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.948 inches and 1.968 inches first hole

Surface Finish:

32.0 microinches grip

Product Name:

Navy special project

Material:

Steel comp 302 spring

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

NSN 5305-00-099-7643

Close Tolerance Screw - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0