## NSN 5305-00-099-7912

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-099-7912 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.165 inches and 0.185 inches **Fastener Length:** Between 0.245 inches and 0.255 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.120 inches and 0.130 inches **Head Height:** Between 0.030 inches and 0.040 inches **Shoulder Diameter:** 0.092 inches first shoulder and 0.093 inches first shoulder **Shoulder Length:** 0.070 inches first shoulder and 0.080 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Astm a582, cond a assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Sd 1069 fscm 35351 mfr ref single treatment response **Thread Series Designator:** Unc Shelf Life: **Unit Of Measure:** 

N/a **Demilitarization:** No

## NSN 5305-00-099-7912

Shoulder Screw - Page 2 of 2



Fiig:

A003b0