
3a

Socket Head Cap Screw - Page 1 of 2





## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.719 inches and 0.844 inches Fastener Length: Between 0.844 inches and 0.875 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.118 inches and 0.130 inches Locking Feature: Pellet threads **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Product Name:** Navy special project **Special Features:** Hole drilled in head 0.048 in. Nom dia Material: Steel comp 4037 or steel comp 8630 **Material Specification:** Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure:

---

## NSN 5305-00-099-8755

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.