NSN 5305-00-100-6291

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-100-6291

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.297 inches and 0.328 inches **Fastener Length:** Between 3.735 inches and 3.765 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.581 inches and 0.635 inches First Diameter From Head: Between 0.310 inches and 0.312 inches **Second Diameter From Head:** Between 0.245 inches and 0.255 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 3.047 inches and 3.077 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 3.436 inches and 3.438 inches **Internal Drive Style:** Torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 2 **Special Features:** Plunger operated spring loaded retaining balls Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unf

NSN 5305-00-100-6291

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0