NSN 5305-00-100-6576



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-100-6576 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.278 inches and 0.328 inches **Fastener Length:** Between 1.606 inches and 1.626 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.126 inches and 0.141 inches **Locking Feature:** Detent ball grip **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches and 0.086 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.188 inches and 1.203 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.511 inches and 1.531 inches first hole **Surface Finish:** 32.0 microinches grip **Product Name:** Navy special project Material: Steel comp 302 spring

Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

NSN 5305-00-100-6576

Close Tolerance Screw - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0