NSN 5305-00-100-6698

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-100-6698 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.140 inches and 0.180 inches **Fastener Length:** Between 0.750 inches and 0.790 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.091 inches and 0.096 inches **Head Height:** Between 0.057 inches and 0.060 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.060 inches Width Across Flats: Between 0.050 inches and 0.051 inches Thready Qty Per Inch (tpi): 80 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-100-6698

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0