NSN 5305-00-101-5698

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-101-5698 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.406 inches **Fastener Length:** Between 0.890 inches and 0.937 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.3765 inches and 0.3813 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees Surface Finish: 32.0 microinches threads **Special Features:** Primer coat applied to head Material: Steel **Surface Treatment:** Cadmium head and chromate head **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response head **Thread Series Designator:** Unf

Shelf Life:

N/a

NSN 5305-00-101-5698

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0