NSN 5305-00-102-4553

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-102-4553

Thread Class:
3a There d Directions
Thread Direction:
Right-hand
Thread Length:
Between 0.657 inches and 0.734 inches
Fastener Length:
Between 1.141 inches and 1.188 inches
Head Style:
Pan
Head Diameter:
Between 0.716 inches and 0.740 inches
Head Height:
Between 0.244 inches and 0.261 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
Between 26.0 rockwell c and 32.0 rockwell c
Screw Material:
Steel comp 8630 or steel comp 4037
Screw Material Specification:
Mil-s-6050 military specification 1st material response or mil-s-8695 military specification 2nd material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416 type 2 class 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
<u></u>
Demilitarization:
No
Fiig:
A500d0

NSN 5305-00-102-4553

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.