NSN 5305-00-102-7584



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-102-7584 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.376 inches and 0.515 inches **Fastener Length:** Between 3.016 inches and 3.063 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or mil-s-8695 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 class 3 federal specification single treatment response **Thread Series Designator:**

	•
Unf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A500d0	

NSN 5305-00-102-7584

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.