NSN 5305-00-103-2994

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-103-2994 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.188 inches and 0.250 inches **Fastener Length:** Between 0.220 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Material Specification:** Astm a574 assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, class 1 military specification single treatment response **Thread Series Designator:** Unrc **Specification Or Standard:** 6 type

Shelf Life: N/a

NSN 5305-00-103-2994

Socket Head Cap Screw - Page 2 of 2



	• -		
In	ıŧ	()t	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.