NSN 5305-00-103-9763

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-103-9763 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.609 inches and 0.766 inches **Fastener Length:** Between 0.734 inches and 0.766 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **Locking Feature:** Pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.312 inches and 0.316 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell c Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 306 fastener or steel comp 316 fasten steel comp xm-7 fastener **Material Specification:** Astm a493 assn standard all material responses fastener **Surface Treatment:** Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response fastener

N/a

Shelf Life:

Unc

Thread Series Designator:

NSN 5305-00-103-9763

Socket Head Cap Screw - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0