Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-104-1679

| Thread Class: |
|---|
| |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.305 inches |
| Fastener Length: |
| 0.875 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.357 inches and 0.373 inches |
| Head Height: |
| Between 0.122 inches and 0.133 inches |
| First Diameter From Head: |
| Between 0.130 inches and 0.140 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.570 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Special Features: |
| Thd end cone point |
| Material: |
| Stainless steel |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Mil-f-14072 e300 military specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5305-00-104-1679

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-f-14072 spec.