

View Online at <https://aerobasegroup.com/nsn/5305-00-104-2784>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.673 inches and 0.765 inches

Fastener Length:

Between 0.735 inches and 0.765 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.303 inches and 0.312 inches

Head Height:

Between 0.185 inches and 0.190 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.190 inches

Width Across Flats:

Between 0.156 inches and 0.159 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell c

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

6 type

Departure From Cited Designator:

As modified by self-locking feature

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0