NSN 5305-00-104-5062

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-104-5062 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.227 inches and 0.327 inches **Fastener Length:** Between 0.297 inches and 0.327 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.172 inches and 0.202 inches **Head Height:** Between 0.172 inches and 0.202 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Special Features:** Threaded hole in head 440 unc-2b; also furnished nut made 4-40 unc-2b 0.172-0.202 in. Dia; 0.057-0.066 in. Lg; lockwasher made of phpspher bronze per astm b139; gold plated; 0.209-0.224 in. Dia; 0.26-0.036 in. Lg 2 reqd Material: Copper alloy 360 **Material Specification:** Qq-b-626 comp 22 federal specification single material response **Precious Material And Location:** gold **Precious Material:** Gold **Surface Treatment:** Gold **Surface Treatment Specification:** Mil-g-45204 type 2 cl 2 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-104-5062

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-g-45204 spec.