**Thread Class:** 

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-104-5072



## 3a **Thread Direction: Right-hand Thread Length:** Between 0.434 inches and 0.500 inches Fastener Length: Between 0.470 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.134 inches and 0.140 inches **Head Height:** Between 0.083 inches and 0.086 inches Locking Feature: Patch threads or pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.086 inches Width Across Flats: Between 0.078 inches and 0.079 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 130000 pounds per square inch Material: Steel fastener Surface Treatment: Cadmium fastener and chromate fastener Surface Treatment Specification: Qq-p-416, type 2 class 2 federal specification single treatment response fastener **Thread Series Designator:** Unc **Specification Or Standard:** 6 type **Departure From Cited Designator:** As modified by locking feature

## NSN 5305-00-104-5072

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

