NSN 5305-00-104-5079

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-104-5079 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.466 inches and 0.641 inches **Fastener Length:** Between 0.609 inches and 0.641 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.642 inches and 0.656 inches **Head Height:** Between 0.430 inches and 0.437 inches **Locking Feature:** Pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.438 inches Width Across Flats: Between 0.375 inches and 0.379 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:**

6 type

NSN 5305-00-104-5079

Socket Head Cap Screw - Page 2 of 2



Departure From Cited Designator	Departure	From	Cited	Designator
---------------------------------	-----------	------	-------	------------

As modified by locking feature

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0