NSN 5305-00-104-5081

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-104-5081

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
1.375 inches	
Fastener Length:	
Between 2.920 inches and 3.000 inches	
Head Style:	
Flat chamfer	
Head Diameter:	
Between 0.642 inches and 0.656 inches	
Head Height:	
Between 0.430 inches and 0.437 inches	
Locking Feature:	
Patch threads or pellet threads or strip threads	
Internal Drive Style:	
Hexagon	
Thread Diameter:	
0.438 inches	
Width Across Flats:	
Between 0.375 inches and 0.379 inches	
Thready Qty Per Inch (tpi):	
14	
Min. Tensile Strength (psi):	
180000 pounds per square inch	
Hardness Rating:	
38.0 rockwell c and 45.0 rockwell c	
Minimum Yield Strength:	
15000 pounds per square inch	
Material:	
Steel fastener	
Surface Treatment:	
Cadmium fastener and chromate fastener	
Surface Treatment Specification:	
Qq-p-416, type 2 class 2 federal specification single treatment response fast	ener
Thread Series Designator:	
Unre	
Specification Data:	
80205-nas1352 professional/industrial association standard	
Shelf Life:	
N/a	

N/a

NSN 5305-00-104-5081 Socket Head Cap Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

Demilitarization:

No

Fiig:

A003b0