## NSN 5305-00-104-9468

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-104-9468 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.125 inches and 0.157 inches **Fastener Length:** Between 0.218 inches and 0.250 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.250 inches **Secondary Washer Outside Diameter:** Between 0.253 inches and 0.263 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.031 inches **Secondary Washer Material Thickness:** Between 0.013 inches and 0.019 inches Material: Steel comp 1060 secondary washer or steel comp 1080 secondary washer **Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416 type 2 cl 3 federal specification single treatment response

## NSN 5305-00-104-9468

Assembled Washer Screw - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unc                       |
| Shelf Life:               |
| N/a                       |
| Unit Of Measure:          |
|                           |

Demilitarization:

No

Fiig:

A003b0