

View Online at <https://aerobasegroup.com/nsn/5305-00-105-0530>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.744 inches and 0.748 inches

Fastener Length:

Between 0.884 inches and 0.888 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.262 inches and 0.270 inches

Head Height:

Between 0.159 inches and 0.164 inches

Hole Diameter:

0.047 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.164 inches

Width Across Flats:

Between 0.141 inches and 0.143 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0