NSN 5305-00-105-4064

Machine Screw - Page 1 of 1



Group

View Online at https://aerobasegroup.com/nsn/5305-00-105-4064

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.310 inches and 0.355 inches
Fastener Length:
Between 0.360 inches and 0.405 inches
Head Style:
Watertight
Head Diameter:
Between 0.270 inches and 0.285 inches
Head Height:
Between 0.070 inches and 0.080 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.112 inches
Features Provided:
O ring and washer
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 85000 pounds per square inch
85000 pounds per square inch
85000 pounds per square inch Screw Material:
85000 pounds per square inch Screw Material: Stainless steel
85000 pounds per square inch Screw Material: Stainless steel Screw Material Specification:
85000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Qq-s-763 federal specification single material response
85000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment:
85000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate
85000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Thread Series Designator:
85000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Thread Series Designator: Unc
85000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life:
85000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a
85000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a
85000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:
85000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:
85000 pounds per square inch Screw Material: Stainless steel Screw Material Specification: Qq-s-763 federal specification single material response Screw Surface Treatment: Passivate Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No