NSN 5305-00-105-6882

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-105-6882 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.219 inches and 0.317 inches **Fastener Length:** Between 1.135 inches and 1.182 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.375 inches and 0.387 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches grip **Special Features:** Aluminum grommet .012 in. Thk on bearing surface of head Steel comp 430fse or steel comp 81b45 or steel comp 4140 or steel comp 302b **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-105-6882

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0