## NSN 5305-00-105-9427

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-105-9427 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.290 inches and 0.330 inches **Fastener Length:** Between 0.585 inches and 0.605 inches **Head Style:** Hexagon **Head Height:** Between 0.115 inches and 0.135 inches Width Between Flats: Between 0.420 inches and 0.460 inches **Shoulder Diameter:** 0.295 inches first shoulder and 0.308 inches first shoulder **Shoulder Length:** 0.245 inches first shoulder and 0.265 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Shoulder Shape:** Round first shoulder **Special Features:** Thd relief 0.200 in. Dia. 0.030 in. Lg Material: Steel comp 416 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

**Demilitarization:** 

No

**Unit Of Measure:** 

## **NSN 5305-00-105-9427** Shoulder Screw - Page 2 of 2



Fiig:

A003b0