## NSN 5305-00-106-6272

Between 0.251 inches and 0.318 inches

Between 0.573 inches and 0.620 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-106-6272

Head Style:
Flat countersunk
Head Diameter:
Between 0.244 inches and 0.279 inches
Grip Diameter:
Between 0.1355 inches and 0.1375 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.138 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Product Name:
Navy special project
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740
Material Specification:
Ams6300 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjc

## NSN 5305-00-106-6272

Close Tolerance Screw - Page 2 of 2



		fe	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0