## NSN 5305-00-108-9698

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-108-9698 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.278 inches and 0.329 inches **Fastener Length:** Between 1.731 inches and 1.751 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.477 inches and 0.492 inches **Head Height:** Between 0.126 inches and 0.141 inches **Locking Feature:** Detent ball grip **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches and 0.086 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.312 inches and 1.328 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.635 inches and 1.655 inches first hole **Surface Finish:** 32.0 microinches grip **Product Name:** Navy special project Material: Steel comp 302 spring **Surface Treatment: Passivate Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

## NSN 5305-00-108-9698

Close Tolerance Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0