## NSN 5305-00-108-9761



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-108-9761 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.460 inches and 0.553 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.284 inches and 0.332 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

**Countersink Angle:** 

Between 99.0 degrees and 101.0 degrees

**Screw Material:** 

Steel

**Screw Material Specification:** 

Q-s-763 federal specification 13th material response or 66 300 series federal specification 2nd material response

**Screw Surface Treatment:** 

Oxide

**Screw Surface Treatment Specification:** 

Mil-c-13924, cl 4 military specification single treatment response

Thread Series Designator:

Unc

**Specification Or Standard:** 

3 type and 3c style

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A500d0

## NSN 5305-00-108-9761

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.