

View Online at <https://aerobasegroup.com/nsn/5305-00-109-7040>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.147 inches and 0.197 inches

**Fastener Length:**

Between 0.270 inches and 0.275 inches

**Head Style:**

Button

**Head Diameter:**

Between 0.303 inches and 0.321 inches

**Head Height:**

Between 0.074 inches and 0.086 inches

**Shoulder Diameter:**

0.183 inches first shoulder and 0.188 inches first shoulder

**Shoulder Length:**

0.078 inches first shoulder and 0.083 inches first shoulder

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Nylon pellet-type element in thds for locking feature

**Material:**

Stainless steel

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response

**Test Data Document:**

03640-6082138 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.