NSN 5305-00-109-7040

View Online at https://aerobasegroup.com/nsn/5305-00-109-7040

Shoulder Screw - Page 1 of 2



Thread Class: 2a **Thread Direction:** Right-hand Thread Length: Between 0.147 inches and 0.197 inches **Fastener Length:** Between 0.270 inches and 0.275 inches **Head Style: Button Head Diameter:** Between 0.303 inches and 0.321 inches **Head Height:** Between 0.074 inches and 0.086 inches **Shoulder Diameter:** 0.183 inches first shoulder and 0.188 inches first shoulder **Shoulder Length:** 0.078 inches first shoulder and 0.083 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder **Special Features:** Nylon pellet-type element in thds for locking feature Material: Stainless steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 military specification single treatment response **Test Data Document:** 03640-6082138 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unc Shelf Life:

--

N/a

Unit Of Measure:

NSN 5305-00-109-7040

Shoulder Screw - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.