Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-110-5623

Thread Class:	
За	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.235 inches a	nd 0.240 inches
Fastener Length:	
Between 0.920 inches a	nd 0.940 inches
Head Style:	
Pan	
Head Diameter:	
Between 0.270 inches a	nd 0.275 inches
Head Height:	
Between 0.070 inches a	nd 0.075 inches
First Diameter From He	
Between 0.143 inches a	nd 0.149 inches
	Bearing Surface Of Head To End Of First Diameter:
Between 0.680 inches a	
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.190 inches	
Thready Qty Per Inch (αi):
32	
Min. Tensile Strength (osi):
160000 pounds per squa	
Externally Relieved Bo	
1	
Material:	
Steel comp 4130 or stee	el comp 4140
Material Specification:	
	d 1st material response or astm a331 assn standard 1st material response or sae assn standard 2nd material
response	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Spe	
	deral specification all treatment responses
Thread Series Designa	
Unf	
Shelf Life:	
N/a	
Unit Of Measure:	

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0