NSN 5305-00-110-5709

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-110-5709 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.990 inches and 1.010 inches **Fastener Length:** Between 3.240 inches and 3.260 inches **Head Style:** Hexagon **Head Height:** 0.281 inches Width Between Flats: 0.625 inches **First Diameter From Head:** Between 0.428 inches and 0.448 inches **Second Diameter From Head:** Between 0.345 inches and 0.350 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.490 inches and 0.510 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.740 inches and 1.760 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel **Material Specification:** Sae gr 8 assn standard single material response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-110-5709

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0