## NSN 5305-00-110-7997

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-110-7997



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.361 inches and 0.453 inches Fastener Length: Between 0.594 inches and 0.656 inches **Head Style:** Round extended washer **Head Diameter:** Between 0.365 inches and 0.385 inches **Head Height:** Between 0.089 inches and 0.099 inches **Extended Washer Diameter:** Between 0.427 inches and 0.447 inches **Extended Washer Thickness:** Between 0.025 inches and 0.030 inches Internal Drive Style: Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 8630 **Screw Material Specification:** Mil-s-6050 military specification single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, ty2 cl3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure:

---

## NSN 5305-00-110-7997

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

