## NSN 5305-00-113-5903

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-113-5903

71101
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.106 inches and 0.183 inches
Fastener Length:
Between 0.234 inches and 0.266 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.218 inches and 0.255 inches
Locking Feature:
Pellet threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.112 inches
Width Across Flats:
0.062 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Countersink Angle:
Between 80.0 degrees and 82.0 degrees
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Unc
Specification Or Standard:
4 type

## NSN 5305-00-113-5903

Socket Head Cap Screw - Page 2 of 2



Departure From Cite	ed Designator:
---------------------	----------------

As mod by locking feature

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0